

OPERATING ORDER SELECTORS SAFELY (Concise)

Leader's Guide, Fact Sheet & Quiz

Item Number: 3963 © AP Safety Training This easy-to-use Leader's Guide is provided to assist in conducting a successful presentation.

PREPARING FOR THE MEETING

Here are a few suggestions for using this program:

- a) Review the contents of the Fact Sheet that immediately follows this page to familiarize yourself with the program topic and the training points discussed in the program. The Fact Sheet also includes a list of Program Objectives that details the information that participants should learn from watching the program.
- b) If required by your organization, make an attendance record to be signed by each participant to document the training to be conducted.
- c) Prepare the area and equipment to be used for the training. Make sure the watching environment is comfortable and free from outside distractions. Also, ensure that participants can see and hear the TV screen or computer monitor without obstructions.
- d) Make copies of the Review Quiz included at the end of this Leader's Guide to be completed by participants at the conclusion of the presentation. Be aware that the page containing the answers to the quiz comes <u>before</u> the quiz itself, which is on the final page.

CONDUCTING THE PRESENTATION

- a) Begin the meeting by welcoming the participants. Introduce yourself and give each person an opportunity to become acquainted if there are new people joining the training session.
- b) Introduce the program by its title and explain to participants what they are expected to learn as stated in the Program Objectives of the Fact Sheet.
- c) Play the program without interruption. Upon completion, lead discussions about your organization's specific policies regarding the subject matter. Make sure to note any unique hazards associated with the program's topic that participants may encounter while performing their job duties at your facility.
- d) Hand out copies of the review quiz to all of the participants and make sure each one completes it before concluding the training session.

3963 OPERATING ORDER SELECTORS SAFELY (Concise) FACT SHEET

LENGTH: 10 MINUTES

PROGRAM SYNOPSIS:

Order selectors, sometimes called order pickers, allow us to move materials, supplies and merchandise to and from storage areas more efficiently than ever before. Like all other powered industrial trucks, they can be extremely hazardous if safe work practices are not followed. Operators of order selectors have a responsibility to operate them in a safe manner at all times. This program examines some common hazards posed by the operation of order selectors and how to control these hazards through safe operating practices.

Topics include order selector stability characteristics, pre-operational inspection, stacking materials properly, fall prevention, safe traveling techniques, preventing injuries to pedestrians and properly parking the vehicle.

PROGRAM OBJECTIVES:

After watching the program, the participant will be able to explain the following:

- How loads and position of the operator's platform affect order selector stability;
- What to check during a pre-operational inspection;
- How to stack materials safely;
- How to properly use fall protection;
- What precautions to take to prevent injuries to pedestrians.

INSTRUCTIONAL CONTENT:

BACKGROUND

- Order selectors come in a variety of sizes, makes and models, each having slightly different design characteristics and control functions; however, most share some of the same features.
- The service brake pedal is located on the floor of the operator's platform and must be depressed for the truck to operate.
- This pedal also acts as a "dead man pedal." When released, the vehicle and all moving parts will stop.
- The pallet clamp is another common feature found on order selectors. This clamp secures the pallet or platform to the truck.
- Driving and operating controls will vary depending on manufacturer. Driving controls allow the truck to move forward and back as well as steer the vehicle; the operating controls allow the operator's platform to be raised and lowered.

OPERATOR TRAINING

- Order selectors may look relatively easy to operate, but like all types of powered industrial trucks, you receive specific training and authorization from your company before use.
- You will be required to successfully demonstrate proper operation of the vehicle in the environment in which it will be used before becoming certified as an operator.

STABILITY CHARACTERISTICS

- As an operator of an order selector, some of the most important things for you to understand are the stability characteristics of the vehicle.
- An order selector typically has rear wheel steering, with a set of load-bearing wheels toward the front, closest to the forks.
- If you draw a line between the load-bearing wheels then back to the midpoint of the rear wheel steering, a triangle is created. This area is referred to as the stability triangle.
- When the combined center of gravity of the order selector, the operator and the load fall inside the stability triangle, the vehicle will be stable.
- If the center of gravity shifts outside the boundaries of the stability triangle, the vehicle is unstable and may tip over.
- An unloaded selector, with an operator, will have a center of gravity near the rear of the stability triangle.

- As the operator's platform is raised, the center of gravity shifts toward the center of the stability triangle; as the platform is lowered the center of gravity shifts back again.
- Placing a load on the forks also causes the center of gravity to shift forward and raising the load shifts it toward the front of the stability triangle.
- This is why it is so important to understand the capacity of your vehicle. Exceeding the vehicle's lifting capacity can easily lead to a tip-over.
- For maximum stability, the load and operator's platform should be lowered before traveling with the vehicle and the order selector should come to a complete stop before raising the platform.

PRE-OPERATIONAL INSPECTION

- Like all powered industrial trucks, the order selector must undergo a pre-operational inspection before use.
- Based on the manufacturer's recommendations, many companies provide a specific checklist for this purpose. If this is the case, be sure to thoroughly inspect all items listed.
- Your inspection should include checking for signs of a fluid leak or any evidence of loose or broken parts.
- All guards and safety devices should be in place and working properly. This includes making sure all warning labels and vehicle's data plate are in place and legible.
- Test the function and movement of all driving and operating controls to ensure they operate as expected.
- Be sure to test the brakes, pallet clamp and horn also.
- If you find anything wrong with the vehicle or fall protection, do not use it. Follow your company's procedure for marking it out of service and reporting the problem.

STACKING MATERIALS CORRECTLY

- Picking, moving and placing loads is the primary task to be performed with the order selector.
- To ensure your load arrives safely at its destination, you must make sure the load is stable and secure before it is moved.
- Never stack, move or place loads that are unstable. Unstable loads can shift and fall, causing damage to the materials and serious injury to workers below.
- Single items, loose parts and other unpackaged materials should be stored in a sturdy, stable container able to safely hold them.
- Crates, boxes and similar items should be arranged in the center of the pallet or platform in a stable configuration.
- Don't try to save a trip by stacking material too high or too close to the edge. Instead, deliver the materials and make two trips rather than risk transporting an unstable load.

USE OF FALL PROTECTION

- One of the most common causes of injury and fatality to operators of order selectors is falling from a raised platform.
- To avoid this, you must always wear your fall harness and have it properly secured to the manufacturer's approved tieoff point any time the operator's platform is elevated.
- Make a habit of connecting your fall protection before going anywhere, even if you do not intend to elevate the platform right away.
- Never disconnect your lanyard in an effort to better reach an object.
- Never connect your lanyard to parts of the rack or shelving. They are not designed for this use and may not hold up to the large force generated should you fall.

SAFE TRAVELING TECHNIQUES

- Operators must keep their hands and feet inside the running lines of the vehicle at all times. Racks, beams and other obstructions can easily crush any body part that comes between it and a moving vehicle.
- Remember that your vehicle is not the only thing moving about the facility. Follow your company's specific traffic regulations to avoid pedestrians, other vehicles and equipment.
- Intersections and blind corners should always be treated with caution. Come to a complete stop and sound your horn before proceeding cautiously into the intersection; this will alert pedestrians and other vehicles of your presence.
- If your facility has mirrors mounted at intersections, be sure to use them before proceeding.
- When traveling behind other vehicles, maintain a safe following distance. A good rule of thumb is to maintain three truck-lengths distance between your truck and another.

PREVENTING INJURIES TO PEDESTRIANS

- Order selectors pose obvious hazards to pedestrians. Your co-workers may not be familiar with the tight turning radius or sudden movements of your vehicle.
- Pedestrians may stand too close or approach the truck while in operation. As an order selector operator, it is your responsibility to keep the safety of pedestrians in mind at all times.
- Always allow pedestrians the right away and make sure all personnel are a safe distance away from your truck before moving.
- Never drive your truck directly towards personnel, especially if they are standing next to solid objects such as machines racks or walls. Pedestrians can be easily crushed when operators ignore this important rule.
- It is also your responsibility to keep pedestrians from standing or walking under a raised load or the raised forks.
- Never allow anyone to ride on your vehicle. Pedestrians just don't realize the dangers and often want a ride; it's up to you to say no.

PARKING THE VEHICLE

- When parking an order selector, even for a moment, you must lower the forks, place the truck in neutral and set the parking brake.
- Most order selectors shift to neutral and set the parking brake when the controls are released. Check the operator's manual to be sure.
- When leaving the truck unattended, which is defined as being more than 25 feet away from the truck or out of plain view, you must also shut off the truck and remove the key to prevent unauthorized use.
- Never park the truck in areas that are not approved by your company. This includes areas with sloped surfaces, in front of stairways, blocking emergency equipment or blocking exits.

OPERATING ORDER SELECTORS SAFELY (Concise)

ANSWERS TO THE REVIEW QUIZ

- 1. b
- 2. c
- 3. a
- 4. b
- 5. b
- 6. a
- 7. b
- 8. c
- 9. b

OPERATING ORDER SELECTORS SAFELY (Concise) REVIEW QUIZ

The following questions are provided to determine how well you understand the information presented in this program.

NameDate	
 The service brake on the operator's platform of an order selector must be released True False 	for the truck to operate.
2. An unloaded selector with an operator will have a center of gravity near thea. Frontb. Middlec. Rear	of the stability triangle.
3. For maximum stability, the load and operator's platform should be lowered beforea. Trueb. False	traveling.
4. When traveling up or down a slope, the load should be facinga. Downhillb. Uphill	
5. When stacking materials, crates and boxes should be arranged in the of the pa. Frontb. Centerc. Rear	pallet of platform.
6. You should never disconnect your lanyard to try and reach an object.a. Trueb. False	
7. You should only connect your lanyard to parts of racks or shelving when you are of force generated should you fall.a. Trueb. False	certain that they can withstand the
 8. A good rule of thumb is to maintain a distance of truck-lengths between you a. 1 b. 2 c. 3 	and other vehicles.
9. Only pedestrians familiar with order selector operation should be allowed to ride you. True b. False	our vehicle.